

**DECLARATION OF PERFORMANCE**  
**IN ACCORDANCE WITH ANNEX III OF REGULATION (EU) 305/2011**  
**NAME OF THE PRODUCT**  
**DEKOPROOF DE- 42**

<b>1. Product Type:</b> Unique identification code of the product-type:	<b>DEKOPROOF DE- 42</b> <b>EN 14891: 2017</b>
<b>2. Type</b> batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	(Batch-No: See product packaging/labelling)
<b>3. Intended use</b> or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	<b>DEKOPROOF DE- 42</b> Dispersion liquid-applied water impermeable product for all external installations beneath ceramic tiling.
<b>4. Name, registered trade name</b> or registered trade mark and contact address of the manufacturer as required under Article 11(5):	<b>DEKOPROOF DE- 42</b>  <b>deKoll Ltd</b> <b>Autostrada Durrës – Tirane, Km 5</b> <b>Xhafzotaj – Durrës</b> <b>Albania</b>
<b>5. Contact Address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)
<b>6. Notified bodies:</b>	Notified testing laboratory, CTEC Center for testing and European Certification LTD
<b>7. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 4 System 3 (for water tightness)

## 8. Declared performance

Essential characteristics	Performance	Test Standard
<b>Initial tensile adhesion strength:</b>	$\geq 0.5 \text{ N / mm}^2$	EN 14891:2017/ A.6.2
<b>Durability of initial tensile adhesion:</b> - against climate/heat ageing action: - against water/humidity action: - against contact with lime water: - against freeze and freeze-thaw cycles:	$\geq 0.5 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$	EN 14891:2017/ A.6.3 / A.6.4 / A.6.5 / A.6.6
<b>Impermeability to water under pressure:</b>	No penetration	EN 14891:2017/ A.7
<b>Release of dangerous substances</b>	Not determined	

## 9.

Parameters	International Standards	Values
<b>Determination of density (Pyknometer metod)</b>	ISO 2811-1: 2023	1.3 g/cm <sup>3</sup>
<b>Determination of viscosity (with Krebs Viscometer)</b>	ISO 2884-1:2024	135-141 Ku
<b>Determination of pH-Value (pH electrodes with glass membrane)</b>	ISO 19396-1:2025	8-9

## 10. Determination of technical data

**Type:** Acrylic based polymer, waterproofing coating

**View:** Liquid paste

**Color:** Green

**Application method:** Brush, roller

**Dilution:** No need for dilution

**Density:** 1.3 g/cm<sup>3</sup>

**Viscosity:** 135-141 Ku

**Consume:** 0.8 Kg/m<sup>2</sup>/ 2 coats

**Drying times:** Touch dry after 2-3 hours and recoatable after 4-6 hours.

**Application temperature:** + 5°C to + 35°C

**Packaging:** It is available in 5 Kg, 15 Kg

**Storage:** 12 months in original packaging in a dry place.

## 11. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 10. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Administrator:

(Name, surname, sign, stamp)

Technical Manager:

(Name, surname, sign, stamp)

## 12. Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

### Further Information

**Contact:** deKoll Ltd

**Tel:** (+355) 44 500 376

**Email:** [info@dekoll.al](mailto:info@dekoll.al)

**www.dekoll.al**

### Legal note:

This information is given in good faith based on dekoll' current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with dekoll' recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Dekoll' reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request

deKoll Sh.p.k

Autostrada Durrës-Tiranë, km 5

(+355) 44 500 376

[info@dekoll.al](mailto:info@dekoll.al)

Certified according to ISO 9001

 **TÜV Rheinland®**  
 Precisely Right.

Page 3