

### **DECLARATION OF PERFORMANCE**

IN ACCORDANCE WITH ANNEX III OF REGULATION (EU) 305/2011

# NAME OF THE PRODUCT PREMIX

No: DEKOLL\_1 08 1100 / 26-09-2024

Product Type:     Unique identification code of the product-type:	PREMIX SSH EN 998-1 :2010	
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	(Batch-No: See product packaging/labelling)	
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Specification for mortar for masonry. Rendering and plastering mortar	
4. Name, registered trade name or	PREMIX	
registered trade mark and contact address of the manufacturer as required under Article 11(5):	deKoll Ltd Autostrada Durres – Tirane, Km 5 Xhafzotaj – Durres Albania	
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)	
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	AVCP 3 According to EN 12004:2012-9, Section 4.4.3, Sistem 3	





7. Notified body (hEN):	Notified testing laboratory, CTEC Center for testing and European Certification LTD.
In case of the declaration of performance (DoP)concerning a construction product covered by a harmonized standard	
8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (see 6)

## 9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonized technical specification
Compressive strength after 28 days	8 N/mm²	EN 12190	
Adhesive strength after 28 days	0.5 N/mm <sup>2</sup>	EN 1542	
Coefficient of water absorption	0.51 kg/m <sup>2</sup> min <sup>0.5</sup>	EN 1015-18:2003	SSH EN 998- 1:2010
Thermal conductivity Part 1	0.61 W/mK	EN 13687	









deKoll sh.p.k Highway Durres –Tirane km 5 , Durres , Albania Tel (+355)44500376

No: 1 08 1100 EN 998-1:2010 PREMIX GP CSIV W0

Specification for mortar for masonry. Rendering and plastering

mortar

Adhesive strength : ≥0.5 N/mm<sup>2</sup>

Compressive strength: CS IV Water absorption: WO

Thermal conductivity : 0.61 W/mK (tab mean value ;P = 50 %)

Water vapour permeability: 1.09.10<sup>-10</sup>

-6.06.10<sup>-11</sup> kg/m2 s Ra

Dangerous substances: see SDS

#### 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:





Administrator:

(Name, surname, sign, stamp)

Technical Manager: (Name, surname, sign, stamp)

## **Ecology, Health and Safety Information (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

Further Information Contact: deKoll Ltd

Tel: (+355) 44 500 376 Email: info@dekoll.al www.dekoll.al

#### Legal note:

This information is given in good faith based on dekoll current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with dekoll recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Dekoll reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request

