

DECLARATION OF PERFORMANCE
IN ACCORDANCE WITH ANNEX III OF REGULATION (EU) 305/2011

NAME OF THE PRODUCT
FUGAPRO
No: DEKOLL_1 18 0010
08/03/2022

1. Product Type: Unique identification code of the product-type:	ULTRAFUGA EN:13888
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	(Batch-No: See product packaging/labelling)
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	ULTRAFUGA FF Grout for tiles. Requirements, evaluation of conformity, classification and designation
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	ULTRAFUGA deKoll Ltd Autostrada Durres – Tirane, Km 5 Xhafzotaj – Durres Albania
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	AVCP 3 According to EN 13888: Section 4.4.3, CWFT for reaction to fire

deKoll Sh.p.k
Autostrada Durrës-Tiranë, km 5
(+355) 44 500 376

--	--

7. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (see 7)
--	----------------------

8. Declared performance

Essential characteristics	Performance	Test Standard	Harmonized technical specification
Compressive strength after dry storage	30.2 MPa	EN 12808-2	EN 13888:2009
Compressive strength after freeze / thaw cycles	21.2 MPa	EN 12808-3	
Flexural strength after dry storage	6.8 MPa	EN 12808-3	
Flexural strength after freeze / thaw cycles	5.2 MPa	EN 12808-3	
Water absorption after 30 minutes:	2.8 MPa	EN 12808-5	
Water absorption after 240 minutes:	5.5 MPa	EN 12808-5	
Shrinkage	2.91 mm/m	EN 12808-4	
Release of dangerous substances	NPD		
Reaction to Fire	A1	EN 13501:2003	

deKoll Sh.p.k
Autostrada Durrës-Tiranë, km 5
(+355) 44 500 376



deKoll sh.p.k Highway
Dr-Tirane km 5 ,
Durrës , Albania Tel
(+355)44500376

EN 13888:2009

FUGA PRO
GROUT FOR TILE

- Compressive strength **≥ 30 MPa**
- Compressive strength
after freeze / thaw cycles **: 21.2 MPa**
- Flexural strength after dry storage: **:6.8MPa**
- Flexural strength after freeze / thaw cycles **: 5.2 MPa**
- Water absorption after 30 minutes: **:2.8 N/mm²**
- Water absorption after 240 minutes: **: 5.5 MPa**
- Shrinkage **:2.91 mm/m**

deKoll Sh.p.k
Autostrada Durrës-Tiranë, km 5
(+355) 44 500 376

info@dekoll.al

Certified according to ISO 9001



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Administrator:
(Name, surname, sign, stamp)

Technical Manager:
(Name, surname, sign, stamp)

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

Further Information

Contact: deKoll Ltd

Tel: (+355) 44 500 376

Email: info@dekoll.al

www.dekoll.al

Legal note:

This information is given in good faith based on deKoll current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with deKoll recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Dekoll reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request

deKoll Sh.p.k
Autostrada Durrës-Tiranë, km 5
(+355) 44 500 376

info@dekoll.al

Certified according to ISO 9001

