

FINISHING



GRAFIATO ACRYLIC LIQUID

Colour	Packaging
White	Bucket 25 Kg

Granulometry	Consumption
1R	2.7 kg/m ²
1V	2.7 kg/m ²
1.5R	3.0 kg/m ²
1.5V	3.0 kg/m ²
2R	3.1 kg/m ²
3R	3.5 kg/m ²

DESCRIPTION

Decorative coating for exterior façade use. It is an ecologically tested product manufactured using HTT technology, which allows the wall to breathe and prevents mold formation. This product does not crack and does not allow dirt to adhere to it, making it very easy to self-clean. GRAFIATO is characterized by the following properties:

- Allows wall breathability to vapor.
- Forms a durable structure.
- Seals cracks in cement-lime based plasters.
- Forms an attractive and protective structure against atmospheric agents.
- Characterized by excellent workability and open time.
- Has a long working time (does not dry quickly).
- Simple and easy to apply.

SUBSTRATE PREPARATION

The surface where GRAFIATO will be applied must first be cleaned of dust as well as residues of oil, grease, varnishes, wax, and adhesive materials. Cleaning is carried out manually. Before applying GRAFIATO, the surface must be smoothed and leveled with Ecoliner or Bondex, and then primed with Astar Grafiato. The substrates must be level and mechanically stable.

FIELD OF APPLICATION

Suitable for creating decorative coatings with very good waterproofing, adhesive, and elastic qualities. It is used for creating decorative coatings over surfaces filled with cement mortar and base thermal insulation mortar.

APPLICATION

The product is mixed until a homogeneous and easily applicable mass is formed. Mixing can be done using a low-speed electric mixer. Care must be taken to ensure the mixer is completely clean from any pigment residues to avoid any color variation in the final product. The product is applied manually using a trowel and worked in a horizontal, vertical, or circular direction depending on the desired aesthetic effect. Workability depends on the ambient temperature.



TECHNICAL DATA

Appearance: Paste	Density: 1,85 ± 0.05 kg/lt
Packaging: Plastic Bucket 25 kg	Adhesive strength: 0.4 N/mm2
Colour: White	Vapor permeability: V3, Low
Flammability: Non-flammable	Durability: 0.8 N/mm2
Resistance to moisture: Good	Thermal conductivity: 0.93 W/(mK)
pH of mixture: 8-9	Water Absorption: W3, Low
Temperatura e aplikimit: +5°C to +35°C and relative humidity below 80%	Storage: Store in places protected from sun exposure. Protect from frost.
Storage Time: 24 months in original packaging and in a cool place.	

