

FINISHING



GRATEX ACRYLIC LIQUID

Colour	Packaging
White	Bucket 25 Kg

DESCRIPTION

Final decorative acrylic coating for use on external facades as well as interior surfaces. This product forms a stable structure, resistant to weather conditions such as sunlight and mold formation, as it allows vapor permeability. It is a simple product to apply, with excellent spreadability and adhesion.

MAIN CHARACTERISTICS

- Stable structure and high resistance to weather conditions.
- Allows vapor permeability, preventing the formation of mold and moisture.
- Easy application, with excellent spreadability and adhesion.
- Creates durable decorative coatings that offer high waterproofing and elasticity.
- Suitable for filling and protecting surfaces covered with cement mortar and thermal insulation plaster.

SUBSTRATE PREPARATION

The surface where GRATEX will be applied must first be cleaned of dust as well as residues of oil, wax, and adhesive materials. The cleaning of the aforementioned is carried out manually. The surfaces must be flat and mechanically stable. Before applying GRATEX, the surface must be leveled and smoothed with Ecoliner or Bondex and then primed with Astar Grafiato.

FIELD OF APPLICATION

Suitable for creating decorative coatings with high-quality waterproofing, adhesion, and elasticity. Used for creating decorative finishes on surfaces filled with cement plaster and base thermal insulation mortar.

APPLICATION

The product is mixed until a homogeneous and easily applicable mass is formed. Mixing can be done with a slow-speed electric mixer. Care must be taken to ensure the mixer is completely clean from residues of different pigments to avoid any variation in the final product's color. The application is done manually using a trowel and worked in a horizontal, vertical, or circular direction depending on the desired aesthetic effect. Ready for use in paste form, available in white or colored versions. Available in various grain sizes.



TECHNICAL DATA

Appearance: Paste	Working time: 20 min in 20°C
Packaging: Plastic Bucket 25 kg	pH of mixture: 8-9
Colour: White	Adhesive Strength: 0.4 MPa
Flammability: Non-flammable	Density: 1,85 ± 0.05kg/lt
Application Temperature: +5°C to +35°C and relative humidity lower than 80%.	Storage Time: 24 months in original packaging. Store in places protected from sunlight. Protect from freezing.
Drying Time: 24-48 hours depending on ambient temperature and humidity.	

