

# FINISHING



# GRATEX SILICONE

Colour	Packaging
White	Bucket 25 Kg

Granulometry	Consumption
1V	2.7 kg/m <sup>2</sup>
15V	3.0 kg/m <sup>2</sup>
15R	3.0 kg/m <sup>2</sup>
2R	3.1 kg/m <sup>2</sup>

## DESCRIPTION

Final decorative silicone layer for use on exterior facades as well as interior surfaces. It is a product that is easy to apply, with very good coverage and adhesion.

## PRODUCT CHARACTERISTICS

- Stable structure and high resistance to weather conditions.
- Allows vapor permeability, preventing mold and moisture formation.
- Easy application and excellent workability.
- Very good coverage and adhesion on various surfaces.
- Improves aesthetics of facades and interiors, providing a beautiful and durable finish.

## SUBSTRATE PREPARATION

The surface where GrateX Silicone will be applied must first be cleaned of dust, as well as residues of oil, wax, and adhesive materials. This cleaning is done manually. The surfaces must be flat and mechanically stable. Before applying this product, the surface should be leveled and smoothed with Ecoliner or Bondex, and then primed with Grafiato Primer.

## APPLICATION METHOD

The product is mixed until a homogeneous and easily applicable mass is formed. Mixing can be done with a slow-speed electric mixer. Care must be taken to ensure the mixer is completely clean from residues of different pigments to avoid any color variation in the final product. The product is applied manually using a trowel and worked in horizontal, vertical, or circular motions depending on the desired aesthetic effect. Ready for application in paste form, white or colored. Available in different grain sizes.



TECHNICAL DATA

<b>Appearance:</b> Paste	<b>Density:</b> 1,85 ± 0.05 kg/lt
<b>Packaging:</b> Plastic Bucket 25 kg	<b>Flammability:</b> Non-flammable
<b>Colour:</b> White	<b>pH of mixture:</b> 8-9
<b>Resistance to moisture:</b> Good	<b>Storage:</b> Store in places protected from exposure to sunlight. Protect from frost.
<b>Application Temperature:</b> +5°C to +35°C and relative humidity below 80%	<b>Drying Time:</b> 24 - 48 hours depending on the temperature and humidity of the environment.
<b>Storage Time:</b> 24 Months in original packaging and in a cool place.	

