

## PËRSHKRIMI

**Stuko Veneciane** është një bojë me bazë uji për sipërfaqe të brendshme, një produkt në formë paste, një teknike dekorative antike e përdorur për të realizuar sipërfaqe të lëmuara dhe me shkëlqim, të ngjashme me shkëlqimin e mermerit.

Produkti shfaqet i ndryshëm sa herë që aplikohet karakterizuar nga tone dhe efekte që varen kryesisht nga vetitë e ustait.

E disponueshme në 32 ngjyra.

### PERGATITJA E SIPERFAQEVE DHE APLIKIMI:

Eliminoni shtresat e vjetra të bojave si tempera etj, hiqni pluhurin, niveloni parregullsitë e sipërfaqes me ultrafinish, krijoni lidhjen me një shtresë Astari Akrilik ose Universal.

Produkti aplikohet duke përdorur një mall inoxi.

Aplikoni 3 shtresa të produktit (2 shtresa bazë + 1 rifiniturë), duke lënë një kohë prej 5 orësh midis një shtrese dhe tjetrës vijuese.

### SPECIFIKIME TEKNIKE:

Temperatura e ajrit: Min. +8 °C / Max. +35 °C dhe lagështia relative e ajrit : <75%.

Koha e tharjes në kushtet e mësipërme: Preket pas 3 orëve, rilyhet pas 5 orëve.

Normat e mbulimit: 0.4-0.8 kg/m<sup>2</sup> për rezultatin final në sipërfaqe të lëmuara si kartonxhes dhe stuko patinimi.

## DESCRIPTION

**Stucco Veneziano** is a water based masonry covering for interiors, a product in paste form, an ancient decorative techniques used to obtain smooth and shiny surfaces, similar to a coating in marble slabs.

The product appears different each time it is applied characterized by tones and effects which depend on the skill of the decorator.

Available in 32 colours.

### PREPARING THE SURFACE AND APPLICATION

Eliminate any raised layers of tempera paints, remove any dust, level any irregularities in the surface with Ultrafinish, bond with a coat of Acrylic or Universal Primer.

The product can be applied using a steel trowel (inox). Apply 3 coats of product (2 base coats + 1 finishing coat), allowing 5 hours between one application and the next.

### TECHNICAL SPECIFICATIONS

Air temperature: Min. +8 °C / Max. +35 °C and relative humidity of the air: <75%.

Drying times in this conditions: Touch dry in 3 hours, coatability after 5 hours.

Spreading rate: 0.4-0.8 kg/m<sup>2</sup> for the finished result on smooth surfaces such as plasterboard and stucco.

**PINTOCOLOR®**  
TUTTI I MIEI COLORI



**STUCCO  
VENEZIANO**

**KATALOG  
NGJYRASH**





S 0505-Y



S 0510-Y10R



S 0520-Y



S 0550-Y



S 0520-B10G



S 0530-B50G



S 1050-B50G



S 2060-B50G



S 0540-Y10R



S 1050-Y



S 1060-Y10R



S 3040-Y50R



S 0520-G50Y



S 0530-G50Y



S 0560-G50Y



S 0560-G10Y



S 1010-Y50R



S 1060-Y50R



S 0560-Y90R



S 1070-Y90R



S 1000-N



S 2500-N



S 5500-N



S 8000-N



S 2050-R50B



S 2060-R20B



S 3050-R30B



S 1085-Y90R



S 1010-R70B



S 0520-R80B



S 0520-R90B



S 2040-R70B



S 1060-Y10R