

## TECHNICAL DATA

**Consistency:** Paste

**Dilution:** Ready for application

**Consumption:** 3–4 m<sup>2</sup>/kg/coat. Depends on the type of surface.

**Application tools:** Trowel, stainless steel spatula

**Application temperature:** Not lower than 10°C and relative humidity not higher than 35%

**Drying time:** The second coat is applied 10 hours after the first coat. Sanding should be carried out 3–4 hours after applying the two coats. Drying times depend on ambient temperature and humidity. Further processing of patinated surfaces can be carried out after 24–48 hours.

**Packaging:** 20 Kg

**Storage conditions:** Store in places protected from direct sunlight. Protect from frost.

**Shelf life:** Up to 12 months, depending on storage conditions

**PINTOCOLOR**<sup>®</sup>  
TUTTI I MIEI COLORI

## ACRYL PINTOFINISH



**PINTOCOLOR**<sup>®</sup>  
TUTTI I MIEI COLORI



Would you like to know more about our products?  
Autostrada Tirane - Durrës, Km 5.  
[www.dekoll.al](http://www.dekoll.al) | [+355 69 606 6656](tel:+355696066656) | [info@dekoll.al](mailto:info@dekoll.al)



## DESCRIPTION

Acrylic patinating filler, lightweight and ready to use, reinforced with additives.

## CHARACTERISTICS

The addition of lightweight fillers to the product:

- Improves workability and ease of sanding
- Reduces the density of the final product, allowing greater surface coverage with less material
- Improves the thermal insulation properties of the substrate
- Provides high adhesion to the supporting surface

Used indoors for patinating and leveling various surfaces such as gypsum boards, concrete, plaster – up to a thickness of 2 mm.

## ADVICE AND PRECAUTIONARY MEASURES FOR USERS

- S2: Keep out of reach of children
- S28: In case of contact with skin, rinse immediately with soap and water or a suitable cleanser
- S26: In case of contact with eyes, rinse immediately with plenty of water and, if necessary, consult a doctor
- S62: If swallowed, seek medical advice immediately and show the product packaging
- S7: Keep container tightly closed after use
- S3/14: Store in cool places
- S51: Ensure good ventilation of the workplace
- S36/37: Wear protective clothing and gloves during use

## WARNING

The material should be applied on drywall only when the substrate is free from moisture-related deviations and storage issues. When applied on plaster, the surface must be fully cured and free from residues.

