

dekoll®

PREMIX PER L'EDILIZIA

MOSAIC 40

TECHNICAL DATA

Appearance: Liquid

Packaging: 25 kg bucket

Color: 40 different combinations

Consumption: 4-5 kg/m²

Granulometry: 1.5 mm

Storage: Store in a dry place

Shelf life: 12 months from production date

Density: 1.7 gr/cm³

Application temperature: +5°C to +35°C.

dekoll®
PREMIX PER L'EDILIZIA



Dëshironi të dini më shumë mbi produktet tona?
Autostrada Tiranë - Durrës, Km 5.
www.dekoll.al | [+355 69 606 6656](tel:+355696066656) | info@dekoll.al



DESCRIPTION

MOSAIC 40 is a decorative finishing coating composed of multicolored granules and an acrylic binder. It is used for decorating walls on interior and exterior surfaces. It is classified according to the EN 15824 standard.

CHARACTERISTICS

1. Very good workability
2. Resistant to atmospheric conditions and UV rays
3. Durable, strong, and long-lasting structure
4. Excellent hydrophobic properties

FIELD OF APPLICATION

MOSAIC 40 is suitable as a final coat on cement-based walls such as cement mortar, lime mortar, traditional old and new mortar, and gypsum boards which must first be leveled with ECOLINER or one of the products from the ETICS (capot) system.

APPLICATION

Before applying MOSAIC 40, the substrate must be clean from dust, oils, or other materials that hinder adhesion. 24 hours before product application, it is recommended to apply a universal primer or ASTAR GRAFIATO. Before use, mix the product with an electric mixer. Application is carried out in a single coat using a stainless steel trowel at grain thickness, followed by pressing the material to create a uniform surface. After placing the product on the substrate, compress it with a metal trowel to achieve the desired surface finish.

