

TECHNICAL DATA

Consistency: Paste

Chemical composition: Acrylic copolymer, special additives and quartz-based fillers

Color: White (can be pigmented in the Pintocolor system)

Use: Ready to apply

Specific gravity: $1.8 \pm 0.05 \text{ g/cm}^3$

Touch-dry time: 4-6 hours (at 23°C and 50% RH)

Recoating time: 12-24 hours depending on atmospheric conditions

Viscosity: 140 KU

Coverage: 1.1 kg/m² (two-coat application)

pH of mixture 9 ±0.5

Gloss: 20 GU

Recommended thickness: 1.5-2 mm (two-coat application)

Scratch resistance: High when protected with PINTO PROTECT PUR 25 system

Water resistance: Excellent after coating with PINTO PROTECT PUR 25

PINTOCOLOR
TUTTI I MIEI COLORI



Dëshironi të dini më shumë mbi produktet tona?
Autostrada Tiranë - Durrës, Km 5.
www.dekoll.al | [+355 69 606 6656](tel:+355696066656) | info@dekoll.al

PINTOCOLOR[®]
TUTTI I MIEI COLORI

**PINTOLUX
MODERN TOUCH**



DESCRIPTION

It is a ready-to-use decorative coating based on acrylic resin, designed to create smooth and modern surfaces for walls and façades. This product is characterized by high coverage and durability, providing different visual effects depending on the application technique. PINTOLUX is easy to use and apply on both horizontal and vertical surfaces. It can be applied as a decorative layer on any type of interior and exterior surface. It can be pigmented in a wide variety of colors through the PintoColor tinting system.

FIELD OF APPLICATION

Used for interior and exterior applications on floors, walls, and stairs. It can be used for coating special substrates such as sinks, furniture, counters, tables, etc. Suitable for applications requiring resistance to vibrations, such as surfaces made of gypsum boards or cement boards, underfloor heating systems, balconies, etc. Applicable in homes, hotels, shops, restaurants, or wherever a modern, elegant, and customized aesthetic appearance is required.

SUBSTRATE PREPARATION AND APPLICATION

The surface must be clean, properly primed, dry, and free from grease or dirt that may hinder proper adhesion. The product is ready for use.

Use a stainless steel spatula. The first coat must be applied evenly to level the substrate. Touch-dry time is 4-6 hours, while recoating time is 12-24 hours depending on environmental conditions. Apply 2 to 3 coats for durable and high-resistance results. Ambient temperature must be between 5°C and 35°C. Do not apply in high humidity conditions.

AFTER USE

S2: Keep out of reach of children - S28: In case of contact with skin, rinse immediately with soap and water or a suitable cleanser - S26: In case of contact with eyes, rinse immediately with plenty of water and, if necessary, consult a doctor - S62: If swallowed, seek medical advice immediately and show the product packaging - S7: Close tightly after application - S3/14: Store in cool places - S51: Ensure good ventilation of the workplace - S36/37: Wear protective clothing and gloves during use



Very low emissions. The product emits very low levels of harmful substances into indoor air.